



HOME

Combi 200
I Saw 215
I Saw 265
Universal 300
Profi 400
Profi 400 HD




Industrie 500
Industrie 500 HD
Industrie 500 HS
Industrie 500 DUO
Mammut 800
Mammut 830

REICH INDUSTRIE 500 DUO




2 PARALLE SCHIEBETISCHE



COMPLETELY MOVABLE TABLE TOP
-CE-certified and GS-tested
-Complies with accident prevention regulations
-removable safety feed (material pusher)
-separately covered saw blade in the operating area
-automatic switch-off and stop of the machine when the wheel covers are opened.
-firmly welded table for better cleaning
-stable table with hygienically designed reinforcements
Built-in wheel scrapers - can be changed without tools
saw blade guide made of wear-resistant material and removable without tools.

- Gas spring tensioning of the saw blade, therefore always correct blade tension.
- All housing parts made of stainless steel.
- The cutting height is approx. 50 mm lower than the standard Industry 500 machine.
- The table top forms the support for the telescopic table.

SCHIEBETISCH MIT TELESKOP-FÜHRUNG



- telescopic table.
- A stable guide unit is formed by corresponding tubes.
- A 30 mm thick solid stainless steel shaft is mounted on this guide unit.
- The table is guided by this shaft and can also be rotated or folded up for cleaning, around this shaft for cleaning.
- In addition, two ball bearings roll on this shaft and 4 each on the machine housing.
- Reinforcements are completely welded to the sliding table.
- The hand guard of the sliding table can be folded down, to achieve a flat table surface accessible from all sides.
- When the hand guard is folded down, the sliding table can no longer be moved.
- Special dimensions can be realized at an extra charge.

- Rim guided by shelves in wheels, therefore no jumping down jumping down possible.

Self-supporting stainless steel housing

- Portion stop removable without tools
- Machine construction without the use of silicone, therefore also absolutely hygienic in the future.
- Electronic wear-free motor brake.

KOMPAKTE AUSFÜHRUNG



- Switch monitoring center for safety solenoids.
 - Safety magnets in separate plastic housing
 - Large ergonomic bow handles for opening the doors.
 - Stainless steel chip box
 - 5 m connection cable with phase inverter plug
 - easy to maintain electrics - with standard components!
- For three-phase current : 230/400 V / 50 Hz.
 Connected load : 3.0 kW
 Speed : 1500 / min.
 Table dimensions : 880 x 900 mm
 Table height : 950 mm
 Cutting speed : approx. 40 meters / second
 Cutting width : 480 mm
 Cutting height : approx. 445 mm
 Belt length : 3800 x 16 x 6 x 0.5 mm
 Housing : stainless steel
 External dimensions : 880 x 1010 x 2000 mm
 Net weight : 395 kg
 Gross weight : 410 kg on pallet.

C.-E. Reich GmbH
Oberer Wasen 13
D-73630 Remshalden

✱

Heute ist Dienstag, der 25 März 2025, 15 Uhr 39

Kontakt:

Phone: +49-7151-79899

Fax: + 49-7151-74692

✱

e-mail: cereich@cereich.de

Homepage: <https://www.cereich.info>

VAT Number: DE146624958

✱



Impressum | AGB | Widerrufsbelehrung und -formular | Liefer- und Zahlungsbedingungen | Datenschutz | Cookie-Richtlinie
Copyright: C.-E. Reich GmbH